

FIREPRO

FIRE PROTECTIVE BUILDING PRODUCTS

HEAD OFFICE: AUCKLAND (09) 579 0367
WELLINGTON (04) 568 7086 • CHRISTCHURCH (03) 379 9364
www.firepro.co.nz sales@firepro.co.nz

CI/SfB

CERAMIC FELT DATASHEET - AUG08

Product specifications
can change. Contact
us to ensure you have
our latest datasheet

CERAMIC FELT GLAZING TAPE

FIREPRO CF1003 & CF2003

DESCRIPTION

Firepro Ceramic Felt Tape is used where wired glass or fire rated glass is installed in a steel frame. It provides a non-combustible cushion for the glass. It is used in conjunction with Firepro M707 intumescent sealant.

The ceramic felt tape is 2mm - 3mm thick and comes in 10M rolls either 10mm or 20mm wide. The ceramic felt has a double sided adhesive tape on one face. In some situations two layers of ceramic felt are used.

CF1003 10mm wide.
CF2003 20mm wide.

LIMITATIONS

1. Where intumescent felt is required use Firepro FIS Intumescent Strip.
2. Ceramic Felt is not recommended for use in glassed timber systems.

Firepro stock several products for this use:

System 90
System 36
FIS Strips
PAL Strips
Intustrip
Flexpress SA Seal

3. Fire test certificates can not be provided as for ceramic felt as it has been fire tested as part of proprietary fire rated window systems.

NOTE: The technical information and suggestions for use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. All dimensions are nominal. We reserve the right to make changes or to withdraw designs and products without notice.