

# FIREPRO CENTABUILD

HEAD OFFICE: AUCKLAND (09) 579 0367  
WELLINGTON (04) 568 7086 • CHRISTCHURCH (03) 379 9364  
[www.firepro.co.nz](http://www.firepro.co.nz) [sales@firepro.co.nz](mailto:sales@firepro.co.nz)

CI/SfB

M755 DATASHEET – AUG 08

Product specifications can change. Contact us to ensure you have our latest datasheet

## CENTABUILD M755 ACOUSTIC SEALANT



Centabuild M755 Acoustic Sealant is a flexible water based product for internal use. It is applied around the perimeter of all partitions and all penetrating items on walls where sound compartmentation is required. It is suitable for concrete, brick, masonry, timber, steel, polystyrene and most wall panel products such as gypsum plaster boards.

Firepro M755 maintains the sound transmission class (STC) of 55 in gaps in partitions.

M755 is not a fire rated sealant. When a Fire Resistance Rating plus acoustic protection is required use Firepro M707 Sealant.

### ADVANTAGES

- Good adhesion to most common building substrates.
- No priming required in most cases.
- Can be applied to damp surfaces.
- Water clean up.
- NON TOXIC, NON HAZARDOUS FORMULA.

### PACKAGING

Packed in 10 litre buckets or 600ml sausage packs for bulk use or in 300ml cartridges for smaller applications.

M755 colour is White.

### COVERAGE

The following table shows the amount of sealant required per lineal metre in the joint sizes shown.

Width x Depth	Litres per Lineal Metre	300ml Cartridge per Lineal Mitre
10 x 10mm	0.1	0.33
20 x 10mm	0.2	0.67
30 x 15mm	0.45	1.5

### PAINTERS GAP FILLER

M755 is also useful as a gap and imperfection filler for painters as it can be readily painted.

### APPLICATION NOTES

Surfaces must be clean, sound, free from dirt, grease, dust or other contaminants. Ideally surfaces should be dry although Centabuild M755 will adhere to damp surfaces (NOT WET).

Priming is not normally required for most substrates. However it is recommended to test the substrate prior to sealing. If priming is necessary use a mixed combination of water and M755 Acoustic Sealant 1:1. Apply to substrate and allow to dry before applying sealant.

Areas adjacent to joints may be masked to ensure neat sealant lines. Masking should be removed immediately after tooling.

Apply a bead of M755 around all perimeters of partitions and all openings and penetrations through partitions. Completely cover the outer side of electrical flush boxes.

Apply sealant to joints by cartridge or bulk loading gun.

Joint groove must be completely filled with sealant.

Uncured sealant may be removed with clean water.

### STORAGE

Do not store below 5°C or above 32°C. When stored in correct conditions unopened containers have a shelf life of 12 months.

### SAFETY

Centabuild M755 Acoustic Sealant is non toxic and non hazardous, but prolonged skin contact may irritate. After use wash with soap and water.

### STC RATING

Centabuild M755 Acoustic Sealant maintains the sound transmission class (STC) of 55 in gaps in partitions.

*NOTE: The technical information and suggestions for use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. All dimensions are nominal. We reserve the right to make changes or to withdraw designs and products without notice.*